

MODEL:UC5-FIP-500100PUSB

Product Description

Feature

Portable/safety/High Efficiency/Low Standby Power Consumption For iPhone 4/4S/5 Erupe Plug Charger

Data sheet

Model No.	UC5-FIP-500100PUSB
AC Input	
Nominal Input Voltage	AC 100V~240V
Input Voltage Range	AC 95V~265V
AC Input Frequency	50-60Hz
DC Output	
Output Voltage	5V
Output Current	1A
Output Power	5W
DC Connector Size	USB
Load Regulation	+/-5%
Ripple Noise	180 Mvp-p
Aging & Test	
Chroma Model 6000 Auto Test	PCB Tin Leaking T/Over-Voltage Test
100% Full Load Burn-in Test, 40±5°C, 4hrs Min.	
Environment	
Operating Temperature	0°C ~40°C
Operating Humidity	5%~95%RH
Storage Temperature	-20°C ~85°C
Storage Humidity	5%~95%RH
Protection	
Over Load Protection	Short Circuit Protection
Over Current Protection	Over Temperature Protection

Suitable model

For Iphone 4/4s/5/5c/5s,For Samsung Galaxy,For HTC

Delivery Payment

1. Delivery Detail:
 Sample order less than 100pcs---3work days
 100-1000pcs---5work days
 More than 1000pcs depends on the order QTY
2. Payment:T/T, Western Union, Order amount more than USD 83333.00 accept pay by L/C