

MODEL:UC11-FIP-510210PUSB

Product Description

Feature

Portable/safety/High Efficiency/Low Standby Power Consumption For Ipad USB Charger

Data sheet

Model No.	UC11-FIP-510210PUSB
AC Input	
Nominal Input Voltage	AC 100V~240V
Input Voltage Range	AC 95V~265V
AC Input Frequency	50-60Hz
DC Output	
Output Voltage	5.1V
Output Current	2.1A
Output Power	11W
DC Connector Size	USB
Load Regulation	+/-5%
Ripple Noise	180 Mvp-p
Aging & Test	
Chroma Model 6000 Auto Test	PCB Tin Leaking T/Over-Voltage Test
100% Full Load Burn-in Test, 40±5°C, 4hrs Min.	
Environment	
Operating Temperature	0°C ~40°C
Operating Humidity	5%~95%RH
Storage Temperature	-20°C ~85°C
Storage Humidity	5%~95%RH
Protection	
Over Load Protection	Short Circuit Protection
Over Current Protection	Over Temperature Protection

Suitable model

To Charge Smart Phone
 To Power Digital Products
 To Power Networking Modem, Hub
 To Power CCTV, DVR, LED Display, Set-top Box, Speaker, Scanner etc.

Delivery Payment

1. Delivery Detail:
 Sample order less than 100pcs---3work days
 100-1000pcs---5work days
 More than 1000pcs depends on the order QTY
2. Payment:T/T, Western Union, Order amount more than USD 83333.00 accept pay by L/C