

MODEL:LA40-FHP-195205P4015

Product Description

Feature

Portable laptop desk Charger 40W series

Data Sheet

Model No.	LA40-FHP-195205P4015
AC Input	
Nominal Input Voltage	AC 100V~240V
Input Voltage Range	AC 95V~265V
AC Input Frequency	50-60Hz
DC Output	
Output Voltage	19.5V
Output Current	2.05A
Output Power	40W
DC Connector Size	4.0*1.5mm
Load Regulation	+/-5%
Ripple Noise	180 Mv-p-p
Aging & Test	
Chroma Model 6000 Auto Test	PCB Tin Leaking T/Over-Voltage Test
100% Full Load Burn-in Test, 40±5°C, 4hrs Min.	
Environment	
Operating Temperature	0°C ~40°C
Operating Humidity	5%~95%RH
Storage Temperature	-20°C ~85°C
Storage Humidity	5%~95%RH
Output/Input Parameters	
Full load 12hours temperature	55°C
Efficiency	85%
No Load Power Loss	<1.5W
Insulation Resistance	>100 MΩ
Hi-pot	AC3000V
Protection	
Over Load Protection	Short Circuit Protection
Over Current Protection	Over Temperature Protection
Warranty:	
2 years Warranty	
Dimensions	
PCS/CTN	50PCS
Outer Size	90 * 38 * 27 MM
Size20 container can load around 23,000 pcs	Size 40 container can load around 46,000 pcs